Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M™ Controlled-Flow Seam Sealer PN 08329, 58329
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 05/07/14
Supercedes Date: 01/29/13

Document Group: 22-2510-0

ID Number(s):

41-0003-6655-3, 41-0003-8024-0, 41-3701-2134-9, 41-3701-2165-3, 60-4550-3057-1, 60-4550-7124-5

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

22-2184-4, 22-2037-4

Revision Changes:
Section 16: Disclaimer (first paragraph) information was modified.
Section 16: Disclaimer (second paragraph) information was modified.
Kit: Component heading paragraph information was modified.
Kit: Component document group number(s) information was modified.
Page Heading: Product name information was modified.
Kit: Product name information was modified.
Kit: ID Number(s) information was modified.
Section 16: Web address information was modified.
Section 1: Address information was modified.
Copyright information was modified.
Telephone header information was modified.

Company Telephone information was modified.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2015,3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-2184-4	**Version Number:**	2.01
Issue Date:	01/29/15	**Supercedes Date:**	05/07/14

SECTION 1: Identification

1.1. Product identifier
3M™ Controlled-Flow Seam Sealer PNs 08329, 58329 (Part B)

1.2. Recommended use and restrictions on use

Recommended use
Sealant

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Serious Eye Damage/Irritation: Category 2A.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark | Health Hazard |

Pictograms

Hazard Statements
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure:
liver |

May cause damage to organs through prolonged or repeated exposure:
endocrine system |

Precautionary Statements
General:
Keep out of reach of children.

Prevention:
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear eye/face protection.
Wear protective gloves.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Get medical advice/attention if you feel unwell.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyether Polyol	9082-00-2	60 - 100 Trade Secret *
Diethyltoluenediamine	68479-98-1	10 - 30 Trade Secret *
Propoxylated Trimethylolpropane	25723-16-4	3 - 13 Trade Secret *
M-xylene-alpha,alpha'-diamine	1477-55-0	1 - 5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
M-xylene-alpha,alpha'-diamine	1477-55-0	ACGIH	CEIL:0.1 mg/m3	Skin Notation
Diethyltoluenediamine	68479-98-1	CMRG	TWA:0.02 ppm(0.13 mg/m3)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended: Butyl Rubber
Fluoroelastomer

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Viscous
Odor, Color, Grade:	Orange-Yellow.
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	>=410 ºF
Flash Point	>=290 ºF [*Test Method:* Tagliabue Closed Cup]
Evaporation rate	<=1 [*Ref Std:* WATER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	*Not Applicable*
Vapor Density	>=1 [*Ref Std:* AIR=1]
Density	1.03 g/ml
Specific Gravity	1.03 [*Ref Std:* WATER=1]
Solubility in Water	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*No Data Available*
Viscosity	1,200 - 1,700 centipoise
Hazardous Air Pollutants	0 % weight [*Test Method:* Calculated]
Volatile Organic Compounds	0 g/l [*Test Method:* calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0 % weight [*Test Method:* calculated per CARB title 2]
Percent volatile	0 % weight [*Test Method:* Estimated]
VOC Less H2O & Exempt Solvents	0 g/l [*Test Method:* calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
None known.

10.5. Incompatible materials
Strong acids
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Endocrine Effects: Signs/symptoms may include disruption of gonadal, thyroid, adrenal, or pancreatic function; changes in hormone production; alterations in circulating hormone levels; and/or changes in tissue response to hormones.

Additional Information:
Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Increased numbers of tumors in the liver, thyroid, and possibly the mammary glands were observed in rats given DETDA (CAS No. 68479-98-1) in their diet for two years.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Polyether Polyol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polyether Polyol	Ingestion	Rat	LD50 > 10,000 mg/kg
Diethyltoluenediamine	Dermal	Rat	LD50 > 2,000 mg/kg
Diethyltoluenediamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.61 mg/l
Diethyltoluenediamine	Ingestion	Rat	LD50 472 mg/kg
Propoxylated Trimethylolpropane	Dermal	Rat	LD50 > 2,000 mg/kg
Propoxylated Trimethylolpropane	Ingestion	Rat	LD50 > 2,500 mg/kg
M-xylene-alpha,alpha'-diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-xylene-alpha,alpha'-diamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-xylene-alpha,alpha'-diamine	Ingestion	Rat	LD50 980 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Diethyltoluenediamine	Rabbit	No significant irritation
Propoxylated Trimethylolpropane	Rabbit	No significant irritation
M-xylene-alpha,alpha'-diamine	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Diethyltoluenediamine	Rabbit	Severe irritant
Propoxylated Trimethylolpropane	Rabbit	Mild irritant
M-xylene-alpha,alpha'-diamine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value

Diethyltoluenediamine	Human	Some positive data exist, but the data are not sufficient for classification
M-xylene-alpha,alpha'-diamine	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diethyltoluenediamine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diethyltoluenediamine	In vivo	Some positive data exist, but the data are not sufficient for classification
M-xylene-alpha,alpha'-diamine	In Vitro	Not mutagenic
M-xylene-alpha,alpha'-diamine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Diethyltoluenediamine	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Diethyltoluenediamine	Ingestion	Not toxic to female reproduction	Rat	NOAEL 3.5 mg/kg/day	24 months
Diethyltoluenediamine	Ingestion	Not toxic to male reproduction	Rat	NOAEL 2.8 mg/kg/day	24 months
M-xylene-alpha,alpha'-diamine	Ingestion	Not toxic to female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not toxic to male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not toxic to development	Rat	NOAEL 450 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
M-xylene-alpha,alpha'-diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not avaliable	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Diethyltoluenediamine	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/kg/day	24 months
Diethyltoluenediamine	Ingestion	endocrine system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 1.4 mg/kg/day	24 months
Diethyltoluenediamine	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.8 mg/kg/day	24 months
Diethyltoluenediamine	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.4 mg/kg/day	24 months
Diethyltoluenediamine	Ingestion	heart | skin | bone,	All data are negative	Rat	NOAEL 3.5	24 months

		teeth, nails, and/or hair | hematopoietic system | immune system | muscles | nervous system | respiratory system			mg/kg/day	
M-xylene-alpha,alpha'-diamine	Ingestion	endocrine system | blood | bone marrow	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	28 days

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. ***As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging.*** *3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and* ***not*** ***the packaging, labeling, or marking requirements.*** *The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.*

SECTION 15: Regulatory information

15.1. US Federal Regulations
Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	C.A.S. No	Regulation	Status
Diethyltoluenediamine (Benzenediamine, ar,ar-diethyl-ar-methyl-)	68479-98-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable
Diethyltoluenediamine	68479-98-1	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations
Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: 2 **Flammability:** 1 **Physical Hazard:** 1 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	22-2184-4	**Version Number:**	2.01
Issue Date:	01/29/15	**Supercedes Date:**	05/07/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable

for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Safety Data Sheet

Copyright,2014,3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-2037-4	**Version Number:**	3.00
Issue Date:	02/14/14	**Supercedes Date:**	04/01/13

SECTION 1: Identification

1.1. Product identifier
3M™ Controlled-Flow Seam Sealer PNs 08329, 58329 (Part A)

1.2. Recommended use and restrictions on use

Recommended use
Sealant

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification
Acute Toxicity (inhalation): Category 4.
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols
Exclamation mark | Health Hazard |

Pictograms

Hazard Statements
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Harmful if inhaled.
Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements
General:
Keep out of reach of children.

Prevention:
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
In case of inadequate ventilation wear respiratory protection.
Wear protective gloves.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Get medical advice/attention if you feel unwell.

Storage:
Store locked up.

Disposal:
Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:
Not applicable

2.3. Hazards not otherwise classified
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

65% of the mixture consists of ingredients of unknown acute oral toxicity.

96% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
1,1'-Methylenebis(Isocyanatobenzene)	26447-40-5	3 - 7 Trade Secret *
Polyurethane Prepolymer	67837-35-8	40 - 70 Trade Secret *
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	15 - 40 Trade Secret *
Urethane Prepolymer	Trade Secret*	1 - 5 Trade Secret *
Benzene, 1,1'-methylenebis[isocyanato-, homopolymer	39310-05-9	1 - 5 Trade Secret *
Carbon Black	1333-86-4	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed
See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters
No unusual fire or explosion hazards are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions
Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities
Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	Amer Conf of Gov. Indust. Hyg.	TWA(inhalable fraction):3 mg/m3	
Carbon Black	1333-86-4	Chemical Manufacturer Rec Guid	TWA:0.5 mg/m3	
Carbon Black	1333-86-4	US Dept of Labor - OSHA	TWA:3.5 mg/m3	

FREE ISOCYANATES	26447-40-5	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	Amer Conf of Gov. Indust. Hyg.	TWA:0.005 ppm	
FREE ISOCYANATES	5124-30-1	Manufacturer determined	TWA:0.005 ppm;STEL:0.02 ppm	

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists
American Indust. Hygiene Assoc : American Industrial Hygiene Association
Chemical Manufacturer Rec Guid : Chemical Manufacturer's Recommended Guidelines
US Dept of Labor - OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Wear protective gloves.
Gloves made from the following material(s) are recommended: Butyl Rubber
Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber
Apron – Nitrile

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties
General Physical Form: Liquid

Specific Physical Form:	Viscous
Odor, Color, Grade:	Low or no detectable odor, black.
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	>=400 ºF
Flash Point	>=290 ºF [*Test Method:* Tagliabue Closed Cup]
Evaporation rate	<=1 [*Details:* Gels with exposure to humidity.]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	<=0.000004 mmHg [@ 68 ºF]
Vapor Density	>=1 [*Ref Std:* AIR=1]
Density	1.04 g/ml
Specific Gravity	1.04 [*Ref Std:* WATER=1]
Solubility in Water	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*Not Applicable*
Decomposition temperature	*No Data Available*
Viscosity	1,400 - 2,000 centipoise
Hazardous Air Pollutants	4.62 % weight [*Test Method:* Calculated]
Hazardous Air Pollutants	0.40 lb HAPS/gal [*Test Method:* Calculated]
Volatile Organic Compounds	0.2 % weight [*Test Method:* calculated per CARB title 2]
Volatile Organic Compounds	2 g/l [*Test Method:* calculated SCAQMD rule 443.1]
Percent volatile	0.17 % weight
VOC Less H2O & Exempt Solvents	2 g/l [*Test Method:* calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Water
Strong acids
Strong bases
Alcohols
Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Harmful if inhaled.
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin Contact:
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Target Organ Effects:

Prolonged or repeated exposure may cause:
Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE 10.1 mg/l
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Dermal	Rabbit	LD50 > 10,000 mg/kg
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.434 mg/l
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	Ingestion	Rat	LD50 9,900 mg/kg
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
1,1'-Methylenebis(Isocyanatobenzene)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.369 mg/l
1,1'-Methylenebis(Isocyanatobenzene)	Ingestion	Rat	LD50 31,600 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
1,1'-Methylenebis(Isocyanatobenzene)	official classification	Irritant
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
1,1'-Methylenebis(Isocyanatobenzene)	official classification	Severe irritant
Carbon Black	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
1,1'-Methylenebis(Isocyanatobenzene)	official classification	Sensitizing

Respiratory Sensitization

Name	Species	Value
1,1'-Methylenebis(Isocyanatobenzene)	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
1,1'-Methylenebis(Isocyanatobenzene)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,1'-Methylenebis(Isocyanatobenzene)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon Black	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. ***As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging.*** *3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and* ***not*** ***the packaging, labeling, or marking requirements.*** *The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.*

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
Dicyclohexylmethane-4,4'-diisocyanate (HMDI) (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	5124-30-1	15 - 40
Dicyclohexylmethane-4,4'-diisocyanate (HMDI)	5124-30-1	15 - 40

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

Ingredient	C.A.S. No.	Classification
Carbon Black	1333-86-4	Carcinogen

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: 2 **Flammability:** 1 **Physical Hazard:** 1 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® III) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® III ratings are to be used with a fully implemented HMIS® III program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	22-2037-4	**Version Number:**	3.00
Issue Date:	02/14/14	**Supercedes Date:**	04/01/13

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com